
Hydraulica 2000 - A



Boasting Two Tonnes Of Lifting Power

One of the most powerful vacuum lifters in the industry, the Hydraulica 2000 comes with a huge 2000kg capacity for lifting heavy-duty glass, metal, plastics and more.

Boasting 210° powered rotation alongside powered hydraulic tilt from vertical to horizontal, the Hydraulica 2000 gives operators ultimate control when lifting heavy loads.

Perfect for lifting large format glass and non-porous plate materials, the Hydraulica 2000 has four to six individual vacuum pumps and low vacuum alert system for added safety.

Cable remote control is included for operation of vacuum suction and release, as well as hydraulic tilt.

Key Features

- Capacity: 2000kg
- Dual circuit vacuum system with four to six on-board maintenance free pumps
- Powered hydraulic 90° tilt from vertical to horizontal
- Powered hydraulic 210° rotation
- 12v rechargeable battery with integral 110v or 240v charger and battery energy gauge
- Audio-visual low vacuum warning
- Cable remote control as standard
- Wheeled stand for transport and storage available
- Individual pads can be isolated for irregular units (reduces safe working load)

37 | SPIDER PLUSTel: +971 4 881 7775

2000kg Safe Working Load





Technical Specifications

| Safe working load capacity: (smooth, clean surface at 60% vacuum) | | | 2000kg* | 1050kg |
|---|---------------------------|---|---|-----------------|
| Number of suction | n cups | cups: | 26 | 14 |
| Suction cup | uction cup description: | | black rubber, not abrasion resistant. | |
| Suction cup diameter diameter: | | | 330mm | |
| Suitable for lifting material properties: | | gastight / non-porous | | |
| | : | surface: | smooth | |
| example: | | glass, plastic boards, ceramic plates, sheet metals, coated boards | | |
| Weight of lifter | | approx: | 500kg | 360kg |
| Depth of lifter depth: | | 380mm | | |
| Rotation rotation: | | 105° left & right powered hydraulic | | |
| Tilt tilt: | | | 90° powered hydraulic | |
| Vacuum system | dual circuit: | | 4 to 6 pumps, 2 vacuum reserve tanks | |
| Voltage | pump: battery charger: | | 12v DC from rechargeable batteries 110v/240v 50/60Hz single phase factory selectable | |
| Standard accessories standard | | | cable remote control, extension arms with pads (increasing the capacity from 1050kg to 2000kg), wheeled stand | |
| * The capacity is 20 | 00kg with | n extensio | on arms and | 26 pads fitted. |

