

LIFT TOP-LIFT CONSTRUCTION



Maximum performance at material transport

For more than 60 years Böcker has offered powerful inclined lifts for the construction industry and having the largest product range worldwide. With its decades of experience in inclined lift technology, Böcker construction lifts provide outstanding quality in combination with maximum performance.

Key Features

- Lifting height up to 20.3 m
- Max. payload 250 kg
- Max. speed 40 m/min
- Easy assembly thanks to low deadweight

Technical Specifications

Model	Top-Lift Basic	Top-Lift Standard	Top-Lift Highspeed
Payload [kg]	150	250	230
Lifting speed [m/min]	25	34	20/40
Lifting height max. [m]	20.30	20-30	20-30
Rope length [m]	44	44	44
Rope diameter [mm]	5	6	6
Voltage [V / Hz]	230/50	230/50	230/50
Control voltage [V]	24	24	24
Weight of drive unit [kg]	47	54	54

Technical Data

Knee joint	Adjustable from 20°- 45°. Heavy duty hardened steel pulleys for long life of rope.
Drive unit Top-Lift Basic	Hoisting speed 25 m/min., suitable for standard and tilting carriage, maximum payload 150 kg.
Standard carriage	For use when there is no need to tilt for unloading. A safety break device prevents the carriage from falling in the event of a rope failure.
Universal platform	Used for the transport of shingles, roof tiles and slate.
Articulated base plates	Perfect positioning due to articulated base. Also available as height adjustable base plates (optional).

20.3m

Lifting Height



Accessories

Tilting bucket 80 litre
(for tilting carriage only)



Sheet platform
90 x 15 x 220 cm



Solar platform
standard



Universal platform 60 x 35 x 85 cm
with protection grating



Universal platform
comfort 70 x 44 x 70 cm



Platform 60 x 85 x 35 cm
with side-flaps

